

F-9820

S C a S a F Fa Ra

| E E, A | |
|-----------|-----------------|
| F l a | RF-9820S |
| F a | 225-2600 MH |
| | 13 |
| C a a /Ba | 25 H -40 M -e e |
| | |
| | |

| |
|--|
| |
| |

T L3Ha C a T a Ra
a - a a f
fa a a a a a .
T a , a -SWaP
a f ,
MANET a a
L -Of-S a a .T
RF-9820S a a a
L3Ha AN/PRC-163
M - a Ha a , a
a a a .

| E, FACE | |
|------------------------------|---------------------------|
| Temperature | -22 F 131 F (-30 C +55 C) |
| Humidity | 2 % |
| Shock | MIL-STD-810G |
| Vibration | MIL-STD-810H |
| Electromagnetic Interference | MIL-STD-461F |

| E, FACE | |
|---------|------------------------|
| Data | USB 2.0, IP e USB |
| Audio | 19 ADF, A d , USB 2.0, |
| Antenna | 50- TNC |
| Display | USB 2.0 |
| Power | OFF, ON, Z, 14 e e |
| Control | WebMMI |

RF-9820S C. a. E. Fa. Ra.
 2022 L3Ha Tec e, I c. 03/2022 SP123C

Te Wae ad Te Wae Tec e, I c. ade a a e e eed ade a f Te Wae
 Tec e, I c. e U ed Sae ad e c e .

N. -E. C. I. a.
 L3Ha Tec e a a e ba ae ace ad defe e ec a , de e e d -e d
 a ee c e , -c ca eed . Tec a de ad a ced defe ea dc e ca
 ec e ac a , a d, ea, ace ad c be d a .